

Claims

What is claimed is:

1. A flow cell for transporting fluid in a radiant
5 energy field, comprising:

(a) a cell structure having a first elongated
tube disposed therein, said first tube
including a radiant energy blocking
portion integral therewith, and a first
10 open channel extending therethrough, such
first open channel forming a continuous
passageway through said cell structure.

2. A flow cell as in Claim 1, including a first
15 end cap that is sealingly engagable with said cell
structure, said end cap having a protrusion extending at
least partially into such first open channel, and a
second open channel substantially aligned with such first
open channel to extend the continuous passageway through
20 said first end cap.

3. A flow cell as in Claim 1, including a second
end cap disposed on, and sealingly engagable with, an
opposing end of said cell structure, said second end cap
25 having a protrusion extending at least partially into
such first open channel, and a third open channel
substantially aligned with such first open channel so as
to extend the continuous passageway through said second
end cap.

30

4. A flow cell as in Claim 2, including a second
tube disposed substantially concentrically about said

209020" 0098900T

enf
92

first tube, and a third tube disposed substantially concentrically around said second tube.

5 5. A flow cell as in Claim 1 wherein said first tube comprises a perfluorinated copolymer.

6. A flow cell as in Claim 4 wherein said second tube comprises PEEK.

10 7. A flow cell as in Claim 4 wherein said third tube comprises FEP.

15 8. A flow cell as in Claim 1 wherein said radiant energy blocking portion is disposed along a length of said first tube.

20 9. A flow cell as in Claim 8 wherein said radiant energy blocking portion is spaced from an inner surface of said first tube by at least about two wavelengths of the radiant energy.

25 10. A flow cell as in Claim 1 wherein said radiant energy blocking portion is chemically bonded to said first tube.

30 11. A flow cell as in Claim 4 wherein said radiant energy blocking portion is chemically bonded to each of said first, second, and third tubes.

12. A flow cell as in Claim 1 wherein said radiant energy blocking portion is disposed at respective end surfaces of said first tube.

10068683.020602

encl
a2
copy

13. A flow cell as in Claim 1 wherein said radiant energy blocking portion includes carbon.

5 14. A flow cell as in Claim 2 wherein said protrusions of said first and second end caps are positioned to displace respective portions of said third layer, thereby forming a fluid-tight seal between said third layer and said protrusions.

10 15. A flow cell as in Claim 3 wherein said second end cap protrusion is displaced from respective ends of said layers, whereby a gap volume is formed for fluid residence therein.

15 16. A flow cell as in Claim 15 wherein said gap volume is calibrated such that radiant energy losses may be standardized in respective flow cells transporting fluids having various indexes of refraction.

20 17. A flow cell as in Claim 1 wherein said first tube is formed through a single-step extrusion process.

25 18. A method of determining sample composition through radiant energy interaction, comprising:

- 30
- (a) providing a cell body having an open bore extending therethrough;
 - (b) providing one or more layers of material lining such open bore, at least one of said layers having a radiant energy blocking portion integral therewith;

10068683-020602

10068683-020602

- 5 (c) attaching one or more end caps to said cell body, said end caps including protrusions extending therefrom, wherein said protrusions extend at least partially into such open bore such that a fluid-tight seal is formed between said one or more material layers and said protrusion, said end caps further including one or more open channels in substantial
- 10 alignment with such open bore;
- (d) transporting sample fluid and radiant energy through such open bore such that the radiant energy passes through the sample fluid; and
- 15 (e) receiving and interpreting the radiant energy that has passed through the sample fluid.

20 19. A method as in Claim 19 wherein said radiant energy blocking portion is chemically bonded to at least one of said layers.

20. A method as in Claim 19 wherein said radiant energy blocking portion comprises carbon.

1006863 .020602

ad
Cat